

User Interface - Bug #3163

Bug # 2596 (New): Implement missing browse quirks.

4GL quirk: browse becomes unusable when an incompatible query is assigned

08/09/2016 04:46 AM - Stanislav Lomany

Status:	New	Start date:	08/09/2016
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:		case_num:	
billable:	No		
vendor_id:	GCD		
Description			

History

#2 - 08/09/2016 04:53 AM - Stanislav Lomany

In 4GL you can re-assign a query which has different kind of DMO classes or even different number of buffers. In most cases that will make the browse widget unusable. But if the new buffer has the same number of fields, 4GL substitutes and displays columns according to their order. For now P2J displays an error and closes the browse.

Testcase:

```
DEF TEMP-TABLE tt FIELD f1 AS INTEGER
                  FIELD f2 AS CHARACTER
                  INDEX idx f1.
```

```
DEF TEMP-TABLE tt2 FIELD f21 AS INTEGER
                   FIELD f22 AS CHARACTER
                   INDEX idx2 f21.
```

```
DEF TEMP-TABLE tt3 FIELD f31 AS INTEGER
                   FIELD f32 AS CHARACTER
                   FIELD f33 AS CHARACTER
                   INDEX idx3 f31.
```

```
def var i as INTEGER.
```

```
CREATE tt. tt.f1 = 1. tt.f2 = "a".
CREATE tt. tt.f1 = 2. tt.f2 = "b".
CREATE tt. tt.f1 = 3. tt.f2 = "c".
CREATE tt. tt.f1 = 4. tt.f2 = "d".
```

```
CREATE tt2. tt2.f21 = 5. tt2.f22 = "e".
```

```
CREATE tt3. tt3.f31 = 6. tt3.f32 = "f".
```

```
DEFINE QUERY q1 FOR tt SCROLLING.
OPEN QUERY q1 FOR EACH tt.
```

```
DEFINE QUERY q2 FOR tt2 SCROLLING.
OPEN QUERY q2 FOR EACH tt2.
```

```
DEFINE QUERY q3 FOR tt3 SCROLLING.
OPEN QUERY q3 FOR EACH tt3.
```

```
DEF BROWSE br QUERY q1
DISPLAY
  tt.f1 tt.f2
  WITH 8 DOWN TITLE "Static browse".
```

```
DEF FRAME fr br
WITH TITLE "Frame" SIZE 70 BY 15.
```

```
ENABLE ALL WITH FRAME fr.
```

```
PAUSE MESSAGE "Press SPACE to assign similar query".
```

```
browse br:query = query q2:handle.
```

```
PAUSE MESSAGE "Press SPACE to assign incompatible query".
```

```
browse br:query = query q3:handle.
```

```
WAIT-FOR WINDOW-CLOSE OF DEFAULT-WINDOW.
```

#3 - 08/11/2016 06:02 PM - Stanislav Lomany

In 4GL functionality that allows to assign another browsed query with other buffers doesn't work for dynamic browses - browse becomes unusable. In P2J it will work.