

Base Language - Bug #5761

replace `ErrorManager.displayError` with `recordOrThrowError` and fix `recordOrShowError` to morph into a `recordOrThrowError` in certain cases.

10/21/2021 12:14 PM - Constantin Asofiei

Status:	New	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:		Estimated time:	0.00 hour
Target version:		case_num:	
billable:	No	version:	
vendor_id:	GCD		
Description			
Related issues:			
Related to Base Language - Feature #4373: finish core OO 4GL support			New
Related to Base Language - Feature #4352: finish progress.lang.apperror and p...			Rejected
Related to Database - Bug #6919: fix <code>ErrorManager.displayError</code> in <code>TempTableBu...</code>			Review

History

#2 - 10/21/2021 12:23 PM - Constantin Asofiei

From #5070-16:

The NPE is because of a `create-like("")` call on a temp-table handle. I need to debug OE and find if the temp-table name is really empty at that step... as after fixing the NPE I get error dialogs displayed, but the report completes.

The main problem is that `ErrorManager.displayError` is used a lot from `p2j.persist` and `p2j.util` packages.

From what I tested in this specific `create-like("")` case, the `recordOrShowError` should have been used. But, in OE if block-level on error undo, throw., an `SysError` is raised - and in FWD, `recordOrShowError` does not do this.

So I need to fix/check two things:

- if `recordOrShowError` must be used instead of `displayError` (at least in `p2j.persist` APIs related to handle methods/attributes)
- fix `recordOrShowError` to throw a `SysError` if block-level on error undo, throw. is set.

From other testing, in the following circumstances this will set `ERROR-STATUS:ERROR` to true or raise a legacy OE error (if `NO-ERROR` is not set):

- block-level on error undo, throw. is set
- `ON ERROR UNDO, THROW` is at the block
- a catch block for `progress.lang.syserror` exists at the block

For the last two, we need to check if the catch or ON clause is required to be at the parent block or anywhere on the stacktrace. The idea is that in these cases, OE raises a `progress.lang.syserror`.

Also, in FWD `ErrorManager.displayError` is used in a lot of places. I found that for some of them, like usage in `p2j.persist` temp-table related classes, was incorrectly determined that the error is displayed and not logged if `NO-ERROR` is used. Although I think there are legitimate cases where `displayError` must be used, we need to review all usages of this in FWD, and see which are the legitimate ones.

#3 - 10/21/2021 01:29 PM - Greg Shah

- Related to Feature #4373: finish core OO 4GL support added

#4 - 10/21/2021 01:29 PM - Greg Shah

- Related to Feature #4352: finish progress.lang.apperror and progress.lang.syserror added

#6 - 11/08/2022 12:46 PM - Constantin Asofiei

- Related to Bug #6919: fix `ErrorHandler.displayError` in `TempTableBuilder` added

#7 - 11/08/2022 12:46 PM - Constantin Asofiei

Added [#6919](#) for the `TempTableBuilder/AbstractTempTable` cases.